



#### Composition

Item	Descripción	Medida	Material	Cantidad
1	Varilla roscada	M 8	Acero SUS304	1
2	Tuerca	M 8	Acero SUS304	3
3	Arandela plana	M 8	Acero SUS304	2
4	Abrazadera plastica	3 x 14 mm	Polipropileno ( PP )	*
5	Manguito DC	9 - 14 mm	Etileno Propileno Dieno ( EDPM )	2
6	Manguito FO	2 x 4,8 mm	Etileno Propileno Dieno ( EDPM )	1
7	Arandela grover	M 8	Acero SUS304	1
8	Anclaje en "U"	*	Acero SUS304	1

#### Normativas

Rango temperatura	- 55 °C + 85 °C
Niebla salina ( partes SUS304 )	IEC 60068-2-10
Inflamabilidad ( parte PP )	UL 94-2014 Clase HB
RoHS	2002/95/EC
Resistencia UV ( partes PP )	Cumplimiento
Resistencia UV ( partes EDPM )	Cumplimiento

#### Referencias

##### 500269

Grapa exterior (torre) híbrida simple [2xDC(9-14mm) + 2xFO(4,8mm)]



##### 500270

Grapa exterior (torre) híbrida doble [2xDC(9-14mm) + 2xFO(4,8mm)]



##### 500271

Grapa exterior (torre) híbrida triple [2xDC(9-14mm) + 2xFO(4,8mm)]

