



## Composition

Item	Descripción	Medida	Material	Cantidad
1	Varilla roscada	M 8	Acero SUS304	1
2	Tuerca	M 8	Acero SUS304	3
3	Arandela plana	M 8	Acero SUS304	2
4	Abrazadera plastica	2 x 17 mm	Polipropileno ( PP )	*
5	Manguito DC	14 - 17 mm	Etileno Propileno Dieno ( EDPM )	1
6	Manguito FO	2 x ( 4 - 7 mm )	Etileno Propileno Dieno ( EDPM )	1
7	Arandela grover	M 8	Acero SUS304	1
8	Anclaje en "U"	*	Acero SUS304	1

## Normativas

Rango temperatura	- 55 °C + 85 °C
Niebla salina ( partes SUS304 )	IEC 60068-2-10
Inflamabilidad ( parte PP )	UL 94-2014 Clase HB
RoHS	2002/95/EC
Resistencia UV ( partes PP )	Cumplimiento
Resistencia UV ( partes EDPM )	Cumplimiento

## Referencias

**500320**  
Grapa exterior (torre) híbrida  
simple [DC(14-17mm) + 2xFO(4-7mm)]



**500321**  
Grapa exterior (torre) híbrida  
doble [DC(14-17mm) + 2xFO(4-7mm)]



**500322**  
Grapa exterior (torre) híbrida  
triple [DC(14-17mm) + 2xFO(4-7mm)]

