



Composition

Item	Descripción	Medida	Material	Cantidad
1	Varilla roscada	M 8	Acero SUS304	1
2	Tuerca	M 8	Acero SUS304	3
3	Arandela plana	M 8	Acero SUS304	2
4	Abrazadera plastica	3 x 14 mm	Polipropileno (PP)	*
5	Manguito DC	9 - 14 mm	Etileno Propileno Dieno (EDPM)	1
6	Manguito FO + ET	4,8 mm + (6 - 7 mm)	Etileno Propileno Dieno (EDPM)	1
7	Arandela grover	M 8	Acero SUS304	1
8	Anclaje en "U"	*	Acero SUS304	1

Normativas

Rango temperatura	- 55 °C + 85 °C
Niebla salina (partes SUS304)	IEC 60068-2-10
Inflamabilidad (parte PP)	UL 94-2014 Clase HB
RoHS	2002/95/EC
Resistencia UV (partes PP)	Cumplimiento
Resistencia UV (partes EDPM)	Cumplimiento

Referencias

500327 Grapa exterior (torre) híbrida simple [DC(9-14mm) + FO(4,8mm) + ET(6-7mm)]	500328 Grapa exterior (torre) híbrida doble [DC(9-14mm) + FO(4,8mm) + ET(6-7mm)]	500329 Grapa exterior (torre) híbrida triple [DC(9-14mm) + FO(4,8mm) + ET(6-7mm)]
		